



COMBAT®

PORTABLE FIRE EXTINGUISHERS

COMBAT® Carbon Dioxide Fire Extinguishers are used on or near electrical equipment because they leave no mess and do not cause any damage. They are effective on Class B, C & E Fires.

CARBON DIOXIDE EXTINGUISHER

(Black Colour Band)




- Approved to BS EN3 by LPCB (UK)
- TPED certified (CE Mark)
- MED certified (Wheel Mark)
- Top Quality Fire Extinguisher (480 hours salt spray test to ISO 9227 for maximum corrosion resistance protection)
- Effective Suppression for Class B,C & E Fires
- Non-Conductive of Electricity
- High Pressure Hardware
- Signal Red (RAL 3000) Epoxy Polyester Powder Coating
- Used for clean area only
- **Optional** : Excellent corrosion resistance models for extremely harsh environment is available

CARBON DIOXIDE EXTINGUISHER

(Black Colour Band)

Extinguishing Model	C-2CSEC	C-5CSEC
Capacity (kg)	2.0	5.0
Extinguishing Medium	Carbon Dioxide	
Propellant Type	Carbon Dioxide	
Fire Rating	34B	55B
Class of Fire	B,C & Electircal	
Test Pressure	250 kgf/cm ²	
Max Working Pressure	60 kgf/cm ²	
Overall Height (mm) +/- 3mm	490	650
Diameter (mm)	114	152
Width (mm)	158	175
Empty Weight (kg)	5.41	12.07
Full Weight (kg)	7.41	17.05
Min. Discharge Time (Sec)	9.4	13.1
Operating Temperature Range	20° C to + 60° C	
Safe Operating Distance	2 meters	
Cylinder Material	Carbon Manganese Steel (CMS)	
LPCB (UK)	✓	✓
TPED (CE Mark)*	✓	✓
MED (Wheel Mark)	✓	✓

TECHNICAL SPECIFICATION



* Pending for approval 4th quarter 2010, please check for confirmation.

The company reserves the right to change the specification without prior notice.

LINGJACK ENGINEERING WORKS PTE LTD

Contact 65 6759 4163 • Facsimile 65 6758 7513 • Website www.combat.com.sg • Email combat@lingjack.com