



COMBAT®

PORTABLE FIRE EXTINGUISHERS

COMBAT® Biodegradable Foam Fire Extinguisher utilizes the best foam SC-1 in its class. It is very effective on class A & B Fires. SC-1 has the ability to form an aqueous film which flows quickly over water-insoluble hydrocarbon fuel surfaces causing rapid fire extinguishment and vapour suppression for Class B Fires. Also it provides excellent penetrating and wetting qualities when used on Class A Fires.

FOAM STORED PRESSURE EXTINGUISHER

(Cream Colour Band)




- Approved to BS EN3 by LPCB (UK)
- TPED certified (CE Mark)
- MED certified (Wheel Mark)
- Top Quality Fire Extinguisher (480 hours salt spray test to ISO 9227 for maximum corrosion resistance protection)
- Effective Suppression for Class A,B Fires (Hydrocarbon Fires)
- Not Applicable for fires involving live electrical equipments
- Signal Red (RAL3000) Epoxy Polyester Powder Coating
- Widely Used for Class B Fires protection such as Paint Shop, Diesel storage, Petrol Tank
- **Optional** : Excellent corrosion resistance models for extremely harsh environment is available

FOAM STORED PRESSURE EXTINGUISHER

(Cream Colour Band)

Extinguishing Model	C-6FSE	C-9FSE
Capacity	6.0Ltr	9.0Ltr
Extinguishing Medium	AFFF Foam	
Propellant Type	Nitrogen	
Fire Rating	8A/113B	34A/233B
Class of Fire	A,B	
Test Pressure	25 kgf/cm ²	
Max Working Pressure	14 kgf/cm ²	
Overall Height (mm)	503	610
Diameter (mm)	181	181
Width (mm)	232	232
Empty Weight (kg)	4.06	4.36
Full Weight (kg)	10.04	13.36
Min. Discharge Time (Sec)	40	60
Operating Temperature Range	+5°C to +60°C	
Safe Operating Distance	2 Meters	
Cylinder Material	Cold Roll Steel Sheet	
LPCB (UK)	✓	✓
TPED (CE Mark)	✓	✓
MED (Wheel Mark)	-	✓

TECHNICAL SPECIFICATION



The company reserves the right to change the specification without prior notice.

LINGJACK ENGINEERING WORKS PTE LTD

Contact 65 6759 4163 • Facsimile 65 6758 7513 • Website www.combat.com.sg • Email combat@lingjack.com