



COMBAT®

PORTABLE FIRE EXTINGUISHERS

COMBAT® Water Fire Extinguishers utilizes the penetrating, soaking and cooling effective of a 4 meters concentrated water stream for effective suppression of Class A Fires. It is an ideal low cost solution to provide Class A protection from all fire involving freely burning materials such as wood, paper or fabric.

WATER STORED PRESSURE EXTINGUISHER

(Red Colour Band)



- Approved to BS EN3 by LPCB (UK)
- TPED certified (CE Mark)
- MED certified (Wheel Mark)
- Top Quality Fire Extinguisher (480 hours salt spray test to ISO 9227 for maximum corrosion resistance protection)
- Effective Suppression for Class A Fires
- Not Applicable for fires involving live electrical equipment
- Signal Red (RAL 3000) Epoxy Polyestred Powder Coating
- Widely Used for class A Fires protection such as Retail Shop, Printing Company, Wood Working Workshop
- **Optional** : Excellent corrosion resistance models for extremely harsh environment is available

WATER STORED PRESSURE EXTINGUISHER

(Red Colour Band)

Extinguishing Model	C-6WSE	C-9WSE
Capacity	6.0Ltr	9.0Ltr
Extinguishing Medium	Water	
Propellant Type	Nitrogen	
Fire Rating	8A	13A
Class of Fire	A	
Test Pressure	25 kgf/cm ²	
Max Working Pressure	14 kgf/cm ²	
Overall Height (mm)	503	503
Diameter (mm)	181	181
Width (mm)	232	232
Empty Weight (kg)	3.76	4.43
Full Weight (kg)	9.76	13.43
Min. Discharge Time (Sec)	40	83
Operating Temperature Range	+5°C to +60°C	
Safe Operating Distance	2 Meters	
Cylinder Material	Cold Roll Steel Sheet	
LPCB (UK)	✓	✓
TPED (CE Mark)	✓	✓
MED (Wheel Mark)	-	✓

TECHNICAL SPECIFICATION



The company reserves the right to change the specification without prior notice.

LINGJACK ENGINEERING WORKS PTE LTD

Contact 65 6759 4163 • Facsimile 65 6758 7513 • Website www.combat.com.sg • Email combat@lingjack.com